NO	DESCRIPTION	DATE
1	0.4D → 0.83	11.26.02
2	CHANGE CHASSIS HOLE DIRECTION	08.23.04









MOUNTING HOLE

NOTES: UNLESS OTHERWISE SPECIFIED
1. BODIES: BRASS PER JIS-C3604
2. CENTER CONTACT: BRASS PER JIS-C3604
   BERYLLIUM COPPER PER JIS-C1730B
3. INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710
4. PART TO BE CLEAN AND FREE OF BURRS

9	NUT	BRASS	1	NICKEL 100μ" MIN.
8	SLEEVE	BRASS	1	GOLD
7	INSULATION II	TEFLON	1	NONE
6	CENTER CONTACT II	BRASS	1	GOLD
5	CHASSIS	BRASS	1	GOLD
4	INSULATION I	TEFLON	1	NONE
3	CENTER CONTACT I	BERYLLIUM COPPER	1	GOLD
2	WASHER	BRASS	1	NICKEL 100μ" MIN.
1	BODY	BRASS	1	NICKEL 100μ" MIN.
NO	*DESCRIPTION*	*MATERIAL*	*Q'TY*	*FINISH*

製圖	DRAWN	TOLERANCE		品名	23-38 0.83 (50Ω) 1	日期	DATE	版次	REV.
	Elvis	.X	±0.2	TITLE			02.22.02		A-2
檢圖	CHECK	.XX	±0.1	單位	UNIT	DWG.NO.	23-0097		
	Monica	.XXX	±0.05		mm(in)				
認定	APPROVAL	ANGLE	±5°	比例	SCALE	ADACTUS			
	Lewis				4:1				