



NOTES: UNLESS OTHERWISE SPECIFIED

1. BODIES: BRASS PER JIS-C3604
2. CENTER CONTACT: BRASS PER JIS-C3604
BERYLLIUM COPPER PER JIS-C1730B
3. INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710
4. PART TO BE CLEAN AND FREE OF BURRS

| | | | |
|----|-------------------|------|------------------|
| 2 | SMT CONNECTORS | 1 | HIROSE UFL/Ø1.13 |
| 1 | 23-38 Ø1.13 <50Ω> | 1 | |
| NO | DESCRIPTION | Q'TY | FINISH |

MOUNTING HOLE

| | | | | | | | | | | | |
|----|----------|-----------|-------|-------|--------|--------------------------|--------------|----------|----|------|--|
| 製圖 | DRAWN | TOLERANCE | | 品名 | | Hirose ufl-FME B/H 110mm | 日期 | DATE | 版次 | REV. | |
| | Elvis | .X | ±0.2 | TITLE | | | | 06.29.04 | | A-0 | |
| 檢圖 | CHECK | .XX | ±0.1 | 單位 | UNIT | DWG.NO. | ADA-3101-110 | ADACTUS | | | |
| | Monica | .XXX | ±0.05 | | mm(in) | | | | | | |
| 認定 | APPROVAL | .XXX | ±0.05 | 比例 | SCALE | | | | | | |
| | Lewis | ANGLE | ±5° | | 4:1 | | | | | | |